


Air Silencers & Breathers

MM, MMS, and MML air silencers reduce exhaust noise by approximately 20%. MMB breather vents prevent contaminants from entering the air component. All models are constructed of sintered bronze (MML are also housed in plastic). MML is designed to have 15% less pressure drop than MM or MMS models. MMP air silencers feature a unique stem for quick connections to tube collets.



MMS Silencers not only serve as sound reducers, but are also low cost speed controls. An adjustable needle valve in the top of each MMS allows for the setting of exhaust rates.

Specifications and Dimensions

Model No.	Pipe Size	Length	Width	Height	Per Box
MM-019	#10-32*	⁴⁵ /64"	⁵ /16" Hex	⁴⁵ / ₆₄ "	20
MMB-125	¹ /8" NPT	⁷ /16 ["]	7 _{/16} " Hex	7 _{/16} "	20
MM-125	¹ /8" NPT	1 ¹ /8"	⁷ /16" Hex	⁷ /16 ["]	20
MMS-125	¹ /8" NPT	29/32"	¹ /2" Hex	1 _{/2} "	20
MML-125	¹ /8" NPT	2 ¹ /8"	13 _{/16} "	13 _{/16} "	20
MMB-250	1 _{/4} " NPT	5/8"	⁹ /16" Hex	9 _{/16} "	10
MM-250	¹ / ₄ " NPT	1 ³ /8"	⁹ /16" Hex	⁹ /16″	10
MMS-250	¹ / ₄ " NPT	111/64"	⁹ /16" Hex	9 _{/16} "	10
MML-250	¹ / ₄ " NPT	2 ¹ /4"	13/16"	13 _{/16} "	5
MMP-250	¹ / ₄ " O.D. Stem	2 ⁴⁷ /64"	13 _{/16} "	13 _{/16} "	1
MMP-006	6mm O.D Stem	2 ⁴⁷ /64"	²³ / ₃₂ "	²³ / ₃₂ "	1
MMB-375	³ /8" NPT	3/4"	11 _{/16} " Hex	11/16"	5
MM-375	³ /8" NPT	1 ¹ /2"	¹¹ / ₁₆ " Hex	11 _{/16} "	5
MMS-375	3 _{/8} " NPT	1 ¹⁷ /64"	¹¹ / ₁₆ " Hex	11 _{/16} "	5
MML-375	³ / ₈ " NPT	3 ⁷ /16"	1 ¹ /4″	1 ¹ /4"	5
MMP-375	³ /8" O.D. Stem	3 ⁷ /64"	23 _{/32} "	23/32"	1
MMP-010	10 mm O.D. Stem	3 ⁷ /64"	²³ / ₃₂ "	23 _{/32} "	1
MMB-500	1/2" NPT	7 _{/8} "	7 _{/8} " Hex	7/8"	5
MM-500	¹ /2" NPT	17/8"	⁷ /8" Hex	7 _{/8} "	5
MMS-500	1 _{/2} " NPT	1 ¹⁷ /64"	7 _{/8} " Hex	7 _{/8} "	5
MML-500	¹ / ₂ " NPT	3 ⁹ /16"	1 ¹ /4″	1 ¹ /4"	5
* Furnished with gasket					

^{*} Furnished with gasket